(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 13 May 2004 (13.05.2004)

PCT

(10) International Publication Number WO 2004/040561 A1

(51) International Patent Classification⁷: G02B 3/10

G11B 7/125,

(21) International Application Number:

PCT/IB2003/004629

(22) International Filing Date: 20 October 2003 (20.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02079589.4 11

1 November 2002 (01.11.2002) EP

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HENDRIKS, Bernardus, H., W. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). STALLINGA, Sjoerd [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


- (74) Agent: COBBEN, Louis, M., H.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GII, GM, IIR, IIU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, IT, IFR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

 as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH,

[Continued on next page]

(54) Title: OPTICAL SCANNING DEVICE



Assimation optical scanning device including an optical element (12) having at least two portions, including a body portion (14) having relatively low birefringence and a wavefront aberration generating portion (16) having a relatively high birefringence, the body portion having an attachment surface on which the wavefront aberration generating portion is formed. The wavefront aberration generating portion (16) has a first surface facing the body portion and a second surface facing away from the body portion, the first and second surfaces being of a different shape so that the thickness of the wavefront aberration generating portion, measured parallel to the optical axis, varies along a direction perpendicular to the optical axis. The thickness of the wavefront aberration generating portion at the optical axis is less than half the thickness of the body portion at said optical axis.